

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
22 May 2003 (22.05.2003)


PCT

(10) International Publication Number
WO 03/042801 A1

- (51) International Patent Classification⁷: **G06F 1/32**, 1/16, H04M 1/04 (72) Inventor: **ADLER, Glenn, J.**; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (21) International Application Number: **PCT/IB02/04748** (74) Agent: **DEGUELLE, Wilhelmus, H., G.**; Internationaal Octrooibureau B.V., Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (22) International Filing Date:
12 November 2002 (12.11.2002)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
09/992,601 13 November 2001 (13.11.2001) US
- (71) Applicant: **KONINKLIJKE PHILIPS ELECTRONICS N.V.** [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: BACKLIGHT SYSTEM ARCHITECTURE FOR MOBILE DISPLAY SYSTEM



(57) Abstract: The present invention provides a mobile display system (20) with an improved backlight system. In one embodiment of the invention, the mobile display system comprises a mobile unit including a flat panel display (14), and a first backlight circuit (41a) for providing light to the display. The first backlight circuit includes a plurality of light sources (42a-42d) disposed near edges of the mobile unit and a single power supply (48c) for powering a pre-selected one of the light sources. The system also comprises a base station (26) capable of being powered by an external power source. The base station includes a second backlight circuit (41b) that comprises at least one power supply for powering the plurality of light sources in the mobile unit when the mobile unit is attached to the base station. This invention keeps the weight and power consumption of the mobile unit low, but allows long battery life at the compromise of display surface light intensity while mobile, and provides high brightness characteristics when docked.

WO 03/042801 A1



European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

Declaration under Rule 4.17:

- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for the following designation CN

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Backlight system architecture for mobile display system

The invention relates to a mobile display system.

Mobile devices, such as mobile and handheld PCs, portable TVs and other mobile Internet appliances, have been widely used in our daily lives. Due to their size and mobility, these devices are particularly convenient to people who travel frequently or need to have access to information at any time or in any location, from the Internet or in a stored database for example. When the AC power is available, mobile devices are typically used in conjunction with a docking station on a desktop or elsewhere in an attached or docked mode. The docking station provides network connections as well as connections to peripheral devices, such as a printer. Because their flexibility of being able to be used in either docked mode or mobile (or undocked) mode, there are requirements for high brightness (with similar luminance as stationary monitors) when the mobile devices are docked and powered by mains power, and for optimization of battery life when they are operated in the mobile mode.

A conventional solution for notebook PCs for example, is to use a dimmable power supply. In this case, the backlight power is regulated based on the condition of the re-charger being attached to the notebook PC. When the notebook PC is used in the mobile mode, the optimization of battery life can be achieved by reduction of power in the backlight. This consequently results in reduction of luminance to 60-80 candela/m². If the notebook PC is plugged into an AC power outlet on the wall, the maximum power of the backlight is increased by increasing the current of the internal lamp or the current duty cycle, relative to its maximum value in the battery operated mode. However, even with the increase of the current the brightness achieved is only in the range of 80-100 candela/m², which is far less bright as compared to that of flat panel monitors powered mains power, which has the luminous intensity of 250 plus candela/m².

Thus, most mobile electronic products today are not able to achieve high brightness, unless both weight and thickness are sacrificed.

Therefore, it is an object of the invention to provide a mobile device that maintains mobile characteristics of low weight, thinness and long battery life, while being

able to provide functionality, e.g., high brightness, of a desktop product when electrical mains are available.

This object is achieved by means of a mobile display system according to the invention, as specified in the independent Claim 1.

5 According to the invention, a base station is provided, comprising a second backlight circuit which is connectable to an external power supply, preferably AC mains, when such a power supply is available. Now, when the mobile unit is attached to the base station, the means in the second backlight circuit are enabled and the backlight intensity of the mobile unit is increased.

10 Further advantageous embodiments are specified in dependent Claims 2-6.

According to a first embodiment of the invention, the mobile display system comprises a mobile unit including a first backlight circuit for providing light to the display. The first backlight circuit includes a plurality of light sources and a first power supply for powering a pre-selected one of the light sources. The base station includes a second backlight
15 circuit that comprises at least one further power supply.

The second backlight circuit is arranged for powering those light sources of the first backlight circuit that are not powered by the first power supply in said first backlight circuit.

20 Thus, the first power supply in the mobile unit may be compact and have a low power consumption allowing for long battery life. When using the mobile unit by itself, the backlight intensity is relatively low. However, when an increased backlight intensity is desired, the mobile unit is attached to the base station, and the latter is connected to an external power source. Thereby, all light sources in the mobile unit are enabled and a high backlight brightness is achieved.

25 The total number of light sources provided in the mobile unit is for example four, one of which is powered by the first power supply in the first backlight circuit. The other three light sources are powered by the further power supply in the second backlight circuit.

30 In a second embodiment, the second backlight circuit itself, and thus the base station, comprises one or more light sources. The second backlight circuit further comprises at least one further power supply for powering said further light sources. The base station and the mobile unit are arranged for coupling light from the one or more further light sources in the base station into the mobile unit, when the mobile unit is attached to the base station.

In this second embodiment, basically only a single light source is required in the mobile unit further reducing its weight. When the mobile unit is attached to the base station, the backlight intensity is increased by means of the further light sources in the base station, the light of which is coupled into the mobile unit by means of a suitable structure.

5 Preferably, such a structure comprises selected surfaces of the base station and mobile unit made in materials capable of coupling light.

Other objects and attainments together with a fuller understanding of the invention will become apparent and appreciated by referring to the following description and claims taken in conjunction with the accompanying drawings.

10 BRIEF DESCRIPTION OF THE DRAWINGS

The invention is explained in further detail, and by way of example, with reference to the accompanying drawings wherein:

FIG. 1 shows a basic configuration of a mobile display system according to one embodiment of the invention;

FIG. 2A shows a mobile display system according to a first embodiment of the invention;

FIG. 2B shows a backlight system for the first embodiment of the invention;

FIG. 3A shows a mobile display system according to a second embodiment of the invention; and

FIG. 3B shows a backlight system for the second embodiment of the invention.

Throughout the drawings, the same reference numerals indicate similar or corresponding features or functions.

25 DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

FIG. 1 shows a basic configuration of a mobile display system 10 according to one embodiment of the invention. Display system 10 comprises a battery powered mobile unit 12 and a mains powered base station 16, which includes an electrical cord 17 for plugging into an AC power outlet or other external power source. Mobile unit 12 has four edges 28a, 28b, 28c and 28d and includes a flat panel display 14. Mobile unit 12 may be either a stand-alone mobile device, e.g., a mobile PC, or a flat panel monitor, e.g., a LCD display, for use with a mobile device. Base station 16 is configured to have a surface 15, a slanted surface 18 and two guiding rails 19a and 19b. Guiding rails 19a and 19b have inner

surfaces 29a and 29b, respectively, facing to each other. Mobile unit 12 can be attached to base station 16 along slanted surface 18 and guiding rails 19a and 19b onto surface 15.

FIG. 2A shows a mobile display system 20 according to a first embodiment of the invention. Display system 20 has the same basic configuration as that of system 10 in FIG. 1 and includes a mobile unit 22 and a base station 26. As shown in FIG. 2A, mobile unit 22 also includes electrical connectors 32a, 32b and 32c. Base station 26 also includes electrical connectors 34a, 34b and 34c and a detection mechanism, e.g., switch 36.

FIG. 2B shows a backlight system 40 for the first embodiment of the invention. Backlight system 40 comprises a backlight circuit 41a in mobile unit 22 and a backlight circuit 41b in base station 26. As shown in FIG. 2B, backlight circuit 41a comprises a plurality of light sources, e.g., lamps 42a, 42b, 42c and 42d respectively located near edges of 28a, 28b, 28c and 28d of mobile unit 22. Although there are only four lamps illustrated, additional lamps may be used and placed along any of edges 28a, 28b and 28d. These lamps may be fluorescent lamps, LEDs or other types of light sources. Backlight circuit 41a also includes a built-in power supply 48c powered by a battery (not shown). Backlight circuit 41b includes a plurality of power supplies 48a, 48b, and 48d. In mobile mode, lamp 42c is used and powered by built-in power supply 48c. In docked mode, in addition to lamp 42c, lamps 42a, 42b and 42d are also used and powered by power supplies 48a, 48b and 48d, respectively, which are connected to an AC power outlet.

In backlight circuit 41b in base station 26, a plurality of backlight power supplies 48a, 48b and 48d are placed close to surface 15 (shown in FIG. 2A) for electrically connecting to connectors 32a, 32b and 32c on mobile unit 22, via connectors 34a, 34b and 34c respectively.

Once mobile unit 22 is attached to base station 26 in docked mode, connectors 32a and 32b are in contact with and connected to connectors 34a and 34b, respectively. In this mode, switch 36 is engaged, signaling base station 26 to power its internal power supplies 48a, 48b and 48d so as to power the lamps inside mobile unit 22, thereby increasing the light output at the viewable surface of display 14. In this embodiment, switch 36 is designed so that no high voltage from the internal power supplies of base station 26 is generated unless mobile unit 22 is fully attached to base station 26. This embodiment allows the use of a single power supply in the mobile unit, keeping weight and power consumption low, but allowing long battery life at the compromise of display surface light intensity.

FIG. 3A shows a mobile display system 50 according to a second embodiment of the invention. This embodiment again has the same basic configuration as that of system

10 in FIG. 1 and includes a mobile unit 52 and a base station 56. Base station 56 also includes a detection mechanism, e.g., switch 57.

FIG. 3B shows a backlight system 60 for the second embodiment of the invention. Backlight system 60 comprises a first backlight circuit 61a in mobile unit 52 and a
5 second backlight circuit 61b in base station 56. Circuit 61a includes a single light source, e.g., lamp 64c, located near edge 28c of mobile unit 52, and a single built-in power supply 68c powered by a battery (not shown). Circuit 61b includes a plurality of additional light sources, e.g., lamps 64a, 64b, and 64d, located close to surfaces 15, 29a and 29b, respectively and a
10 plurality of additional power supplies 68a, 68b and 68d. In mobile mode, lamp 28c is used and powered by built-in power supply 68c. In docked mode, in addition to lamp 64c, lamps 64a, 64b and 64d are used and powered by power supplies 68a, 68b and 68d, respectively, which are connected to an AC power outlet. All of these lamps may be fluorescent lamps, LEDs or other types of light sources.

In this second embodiment, surfaces 28a, 28b and 28d of mobile unit 52 may
15 be constructed of, for instance, transparent or translucent material, capable of coupling light from outside of mobile unit 52 into the backlight structure of the unit. Alternatively, the complete encasing plastics of mobile unit 52 may be made of such transparent or translucent material. Surfaces 15, 29a and 29b of base station 56 may also be constructed of materials capable of coupling light from the lamps 64a, 64b, and 64d, out of base station 56, into
20 mobile unit 52. When mobile unit 52 is attached to base station 56 in docked mode, switch 57 is activated and lamps in base station 56 are powered. This causes light to be optically coupled into mobile unit 52 through surface pairs 28a/15, 28b/29b, and 28d/29a, thereby increasing light output at the viewable surface of display 14.

This embodiment allows the use of a single power supply and a single light
25 source in the mobile unit, keeping weight and power consumption low, but allowing long battery life at the compromise of display surface light intensity.

While the invention has been described in conjunction with specific
embodiments, it is evident that many alternatives, modifications and variations will be
apparent to those skilled in the art in light of the foregoing description. Accordingly, it is
30 intended to embrace all such alternatives, modifications and variations as fall within the spirit and scope of the appended claims.

CLAIMS:

1. A mobile display system (20), comprising:
a mobile unit (22) capable of being powered by a battery, and a base station (26) capable of being powered by an external power source;
a first backlight circuit (41a) in the mobile unit (22), the first backlight circuit including a light source disposed near an edge of the mobile unit (22) and a first power supply (48c) for powering said light source, and
a second backlight circuit (41b) in the base station (26), the second backlight circuit being connectable to the external power source and comprising means for increasing a backlight intensity in the mobile unit (22) when said mobile unit (22) is attached to the base station (26).
2. The mobile display system (40) of claim 1, wherein the first backlight circuit comprises a plurality of light sources (42a-42d), a pre-selected one of said light sources (42c) being powered by the first power supply (48c), and the means in the second backlight circuit comprise at least one further power supply (48a, 48b, 48d) for powering the other light sources (42a, 42b, 42d) in the first backlight circuit, when the mobile unit (22) is attached to the base station (26).
3. The mobile display system (40) of claim 1, wherein the means in the second backlight circuit comprise one or more light sources (64a,64b,64d) disposed near edges of the base station (26), and at least one further power supply (68a,68b,68d) for powering said one or more light sources (64a,64b,64d), the base station (26) and the mobile unit (22) being arranged for coupling light from said one or more further light sources into the mobile unit (22).
4. The mobile display system (40) of Claim 3, wherein the base station (26) and the mobile unit (22) have selected surfaces (15,29a,29b; 28a,28b,28d) made in materials capable of coupling light.

5. The mobile display system of claim 1, wherein the base station (26) further includes a detection mechanism (36) for detecting whether the mobile unit (22) is attached to the base station (26).
- 5 6. The mobile display system of claim 1, wherein the mobile unit (22) comprises a flat panel display (14).

1/5




FIG. 1

2/5




FIG. 2A

3/5




FIG. 2B

4/5




FIG. 3A

5/5




FIG. 3B

INTERNATIONAL SEARCH REPORT

Intern al Application No

PCT/IB 02/04748

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 G06F1/32 G06F1/16 H04M1/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G06F G02F H04M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 6 151 008 A (ZHANG TIM L) 21 November 2000 (2000-11-21) abstract; figures 1,2,10 column 2, line 50 -column 2, line 53 column 4, line 10 -column 4, line 14 column 4, line 23 -column 4, line 25	1-6
A	US 6 301 106 B1 (LICHTENWALTER GUY ET AL) 9 October 2001 (2001-10-09) figure 1	1-3,5,6
A	EP 1 152 319 A (PACE MICRO TECH PLC) 7 November 2001 (2001-11-07) abstract; claims 6,7; figure 1	4
	--- -/-	

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"G" document member of the same patent family

Date of the actual completion of the international search

10 March 2003

Date of mailing of the international search report

18/03/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Pohl, M

INTERNATIONAL SEARCH REPORT

International Application No

PCT/IB 02/04748

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 493 685 A (ZENDA HIROKI) 20 February 1996 (1996-02-20) abstract; figure 1 column 2, line 43 -column 2, line 48 column 3, line 14 -column 3, line 17 -----	1-6
A	EP 0 496 383 A (SONY CORP) 29 July 1992 (1992-07-29) the whole document -----	1
A	US 5 854 617 A (CHOI YUN-HO ET AL) 29 December 1998 (1998-12-29) the whole document -----	1

Form PCT/ISA/210 (continuation of second sheet) (July 1992)

INTERNATIONAL SEARCH REPORT

Intern

Application No

PCT/IB 02/04748

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 6151008	A	21-11-2000	NONE	
US 6301106	B1	09-10-2001	NONE	
EP 1152319	A	07-11-2001	EP 1152319 A1	07-11-2001
			US 2001041589 A1	15-11-2001
US 5493685	A	20-02-1996	JP 3245180 A	31-10-1991
			US 5386577 A	31-01-1995
			EP 0443083 A2	28-08-1991
			KR 9400605 B1	26-01-1994
EP 0496383	A	29-07-1992	JP 3128001 B2	29-01-2001
			JP 4348384 A	03-12-1992
			JP 3045187 B2	29-05-2000
			JP 4256921 A	11-09-1992
			CA 2059498 A1	23-07-1992
			EP 0496383 A2	29-07-1992
US 5854617	A	29-12-1998	KR 148053 B1	15-09-1998
			CN 1145483 A	19-03-1997

THIS PAGE BLANK (USPTO)